

RFL-C20000M-HP

Raycus High Performance 20000W Multi Module CW Fiber Laser

Data Sheet V1.0

The Raycus HP series high performance CW fiber lasers are aimed at high-end industry worldwide market, with high stability, high safety standards, high redundancy, and high intelligence. At present, this series of lasers has been purchased and applied in bulk by many internationally well-known equipment integrators.

This highest power segment is designed for ultra-high power industrial applications, such as thick plate cutting, large-scale construction projects, and specialized industrial processes requiring maximum power and efficiency. For industries requiring the ultimate in laser power and performance, this segment provides unparalleled capabilities. It ensures efficient handling of the most challenging materials and processes, pushing the boundaries of what's possible in industrial laser applications.



Product Features

- CE Certification
- PLD certification
- Multiple Anti-high Reflection Mechanisms
- High Intelligent Monitoring Capability
- EtherCat / Profinet / Profibus / DeviceNet
- High Electron-optical Efficiency
- High Power Stability
- Better Performance in Industrial Applications

Product Applications

- ◆ Industrial Cutting
- ◆ Industrial Welding
- ◆ Scientific Research

Technical Specifications

| | | | |
|----------------------|-----------------------|-----------------------|--------------------------|
| Central wavelength | 1075-1085 nm | Supply voltage | 360~510 V AC |
| Output power | 20000 W | Operation mode | CW / Modulate |
| Power instability | ±1 % | Control mode | BUS, Ethernet, RS232, AD |
| Range of power | 10-100 % | Dimensions | 960×1530×1160 mm |
| Repetition frequency | 50-2000 Hz | Weight | <700 kg |
| Beam quality | <4.3 BPP | Operating temperature | 10 - 40 °C |
| Terminal type | QP (Customizable) | Storage temperature | -10 - 60 °C |
| Fiber length | 30 m (Customizable) | Humidity | 30~70 % |
| Fiber core | 100 μm (Customizable) | Cooling method | Water |

Product Dimensions

